

# Communicate anywhere™

## 750CM SB

The Faria WatchDog® 750CM SB is a powerful Iridium Satellite and GPS, tracking, navigation, monitoring, communication and emergency notification system which supports e-mail, internet, and forms reporting.



**The Watchdog™ is a rugged, weather resistant MTU, (Mobile Transmitting Unit), with very low-power draw, providing near real-time secure position and status reports anywhere in the world. Report frequency is user selectable and changeable on-the-fly from once per minute to once per day, (OTA).**

The Faria WatchDog® 750CM-SB provides cost effective text messaging, e-mail and forms reporting via the optional Faria VTERM™.

The Watchdog MTU is designed to meet the demanding requirements of SAE J-1455 "Recommended Environmental Practices for Electronic Equipment Design in Heavy-Duty Vehicle Applications".

### Key Features

- The WatchDog™ can be installed on any vehicle.
- 9-32 volts DC operation with built-in power management programming to ensure low power consumption.
- Three inputs to monitor your vehicle's battery, tank levels, intrusion systems, etc.
- Reports low battery, entry violations, Geo-fence violations, emergency conditions, check engine notifications when broadcast by ECU to [www.watchdogtracking.com](http://www.watchdogtracking.com) for action.
- On-board J1939 CAN interface to monitor the engine and report diagnostic codes to your web site.
- Provides daily status and position reports with mapping, position history, message logs, via a secured log-in on [www.watchdogtracking.com](http://www.watchdogtracking.com)
- A state-of-the-art Iridium Satellite wireless vehicle tracking system that provides an end-to-end solution that empowers you to manage your entire fleet or a single vehicle near real-time anywhere in the world via an easy to use, web-based application.

## 750CM SB

### Features

U-blox 16 Channel GPS for highly accurate positioning

Iridium Satellite Modem Powered by Quake

Low Power Draw - .18 amp/hour

- On-board power conditioning
- Reverse polarity protected
- Re-settable internal Fuse

Interface - Weather resistant Deutsch, DT Series connectors for power cables.

Compact, rugged injection molded case. IP-66 Rated

4 MB (upgradeable) of on-board compact flash RAM for GPS position logging and storage (60,000 capacity)

### Specifications

MQX operating system

4 Integral holes for mounting, hardware included

Voltage: 12 + 24V ready, (9.5 - 36 VDC power)

Operating temperature of -20 to +85°C

Storage Temperature -40 to +85°C

Humidity: 90% RH at 29°C for 24 hours

Shock Resistant per MIL-STD-202, 50G

Vibration Resistant per SAE J1455

Water and Weather Resistant IP-64

Corrosion Resistant per ASTM-B117-73, 48 Hr



## Range of accessories

### FARIA VTERM™

- 7-inch WVGA TFT color display with an integrated touch-screen. Use the display for text messaging, forms reporting and e-mail.

### 2-inch User Interface

- Displays system status, when unit detects a GPS fix and an open communication channel. Can send emergency notifications.

Dealer information:

For further information about FARIA Watchdog®

Telephone 1300 859 632

Facsimile 1800 303 701

E-Mail [support@satcomms.com.au](mailto:support@satcomms.com.au)

